

2.1. Item 5: VRT-24"DX378"L-125# VT

<u>DESIGN CONDITIONS</u>	QTY	DDESCRIPTION	SERIES	SERVICE
DESIGN PRESSURE: 125 PSI DESIGN TEMP: 200/-20°F CA: NONE HEAT TREAT: NONE RADIOGRAPH: HYDRO TEST: 162 1/2 PSI CONTENTS: NAT GAS GRAVITY: .7 SHELL MAT'L: SA-53E/B HEAD MAT'L: SA-516-70 EMPTY WEIGHT: lb. CAPACITY: Gal.	1	FLANGE - 8" RFSO	150#	CLEANOUT
	1	FLANGE - 3" RFSO	150#	INLET
	1	FLANGE - 3" RFSO	150#	OIL OUT
	1	PIPE - 3"	SCH 40	GAS OUT
	1	PIPE - 2"	SCH 40	DRAIN
	1	CPLG - 2" FULL	3000#	SENSOR
	1	CPLG -2" HALF	3000#	HIGH LEVEL
	2	CPLG -2" HALF	3000#	SKIRT VENT
	1	CPLG - 1" FULL	3000#	RELIEF
	6	CPLG - 1/2" FULL	3000#	SIGHT GLASS
	1	CPLG - 3/4" FULL	3000#	PRESSURE
	1	CPLG - 2" FULL	3000#	RELIEF

