

2.2. Item 6: 72"DX240"L-75# HORZ-TREATER

<u>DESIGN CONDITIONS</u>		QTY	DESCRIPTION	SERVICE
DESIGN PRESSURE: 75 PSI		1	4" SCH 40 PIPE/4" 150# RFSO	INLET
DESIGN TEMP: 200/-20°F		1	1" 3000# FULL CPLG	GAS OUT
CA: NONE		1	2" 3000# FULL CPLG	OIL OUT
HEAT TREAT: NONE		1	3" SCH 80 PIPE/3" 150# RFSO	WATER OUT
RADIOGRAPH: NONE		1	1" 3000# FULL CPLG	MAKE UP GAS
HYDRO TEST: 98 PSI		1	3" SCH 80 PIPE/3" 150# RFSO	RELIEF
CONTENTS:		2	2" 3000# FULL CPLG	LIT
GRAVITY:		1	2" 3000# FULL CPLG	PRESSURE
SHELL MAT'L: SA-516R70		1	2" 3000# FULL CPLG	LLSD
HEAD MAT'L: SA-516 GR70N		2	4" SCH 40 VICTAULIC	ANODE
EMPTY WEIGHT: 13,500 lb.		1	18" MANWAY	MANWAY
CAPACITY: Gal.		1	1" 3000# FULL CPLG	THERMOSTAT
		1	1" 3000# FULL CPLG	SPARE
		1	3/4" 3000# FULL CPLG	THERMOMETER
		1	1" 3000# FULL CPLG	PRESSURE
		1	26 3/4" X 55 3/4" FIREBOX	FIRETUBE
		1	1" 3000# FULL CPLG	PRESSURE
		1	1" 3000# FULL CPLG	OIL DRAIN
		4	1/2" 3000# FULL CPLG	SIGHT GLASS
		1	2" 3000# FULL CPLG	DRAIN
		3	2" 3000# FULL CPLG	HLSD/LLSD
		1	2" 3000# FULL CPLG	LLSD



